

Overview

Models

HP 1910-48G Switch	JE009A
HP 1910-24G-PoE (365 W) Switch	JE007A
HP 1910-24G-PoE (170 W) Switch	JE008A
HP 1910-24G Switch	JE006A
HP 1910-16G Switch	JE005A
HP 1910-8G Switch	JG348A
HP 1910-8G-PoE+ (65W) Switch	JG349A
HP 1910-8G-PoE+ (180W) Switch	JG350A
HP 1910-24 Switch	JG538A
HP 1910-8 Switch	JG536A
HP 1910-48 Switch	JG540A
HP 1910-8-PoE+ Switch	JG537A
HP 1910-24-PoE+ Switch	JG539A

Key features

- Customized operation using intuitive Web interface
- Layer 3 static routing with 32 routes for network segmentation and expansion
- Access control lists for granular security control
- Spanning Tree: STP, RSTP, and MSTP
- Lifetime warranty

Product overview

The HP 1910 Switch Series are advanced smart-managed fixed-configuration Gigabit and Fast Ethernet switches designed for small businesses in an easy-to-administer solution. By utilizing the latest design in silicon technology, this series is one of the most power-efficient in the market.

The series has 13 models: eight gigabit and five Fast Ethernet. 8-, 16-, 24-, and 48-port 10/100/1000 models are equipped with additional Gigabit SFP ports for fiber connectivity; in addition to non-PoE models, the 8- and 24-port gigabit models are available with two different levels of PoE, or without. The 10/100 models are available with 8, 24 and 48 ports, and come with two additional combo uplink ports; the 8- and 24-port fast ethernet models are available with or without PoE.

The HP 1910 Switch Series is a great value, with features to satisfy even the most advanced small business network. All models support rack mounting or desktop operation. Customizable features include basic layer 2 features like VLANs and link aggregation as well as advanced features such as Layer 3 static routing, IPv6, ACLs and Spanning Tree Protocols. These switches come with a lifetime warranty covering the unit, fans, power supplies and 24X7 phone support for first three years.

Features and benefits

Management

- **Simple Web management**
allows for easy management of the switch- even by nontechnical users- through an intuitive Web GUI; http and secure http (https) is supported

Overview

- **Single IP management**
enables management of up to four HP 1910 devices using a single Web interface; simplifies management of multiple devices
- **Secure Web GUI**
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **SNMPv1, v2c, and v3**
facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station
- **Complete session logging**
provides detailed information for problem identification and resolution
- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading
- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **Management security**
restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **Network Time Protocol (NTP)**
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **Limited CLI**
enables users to quickly deploy and troubleshoot devices in the network
- **RMON**
provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Default DHCP client mode**
allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of DHCP server on the network, the switch will fallback to a unique static address determined by the MAC address of the switch

Quality of Service (QoS)

- **Broadcast control**
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- **Rate limiting**
sets per-port ingress enforced maximums and per-port, per-queue minimums
- **Traffic prioritization**
provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to four hardware queues for more effective throughput

Connectivity

- **IPv6**
 - **IPv6 host**
enables switches to be managed and deployed at the IPv6 network's edge
 - **IPv6 routing**
supports IPv6 static routes
 - **MLD snooping**
forwards IPv6 multicast traffic to the appropriate interface, preventing traffic flooding
 - **IPv6 ACL/QoS**
supports ACL and QoS for IPv6 network traffic

Overview

- **Auto-MDI/MDIX**
adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports
- **IEEE 802.3X flow control**
provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node
- **IEEE 802.3af Power over Ethernet (PoE) ready**
provides up to 15.4 W per port to power standards-compliant IP phones, wireless LAN access points, Web cameras, and more (all PoE models)
- **IEEE 802.3at Power over Ethernet (PoE+)**
provides up to 30 W per port which allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments.
(Note: applies to all PoE models, except the two 24G-PoE models which support a pre-standard implementation of PoE+)
- **Packet storm protection**
protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Cable diagnostics**
detects cable issues remotely, using a browser-based tool

Security

- **Advanced access control lists (ACLs)**
enables network traffic filtering and enhances network control using MAC- and IP-based ACLs; time-based ACLs allow for greater flexibility with managing network access
- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X and RADIUS network logins**
controls port-based access for authentication and accountability
- **Automatic VLAN assignment**
assigns users automatically to the appropriate VLAN based on their identity, location and time of day
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP root guard**
protects the root bridge from malicious attacks or configuration mistake
- **Automatic denial-of-service protection**
monitors for malicious attacks and protects the network by blocking the attacks
- **Management password**
provides security so that only authorized access to the Web browser interface is allowed

Performance

- **Half-/full-duplex auto-negotiating capability on every port**
doubles the throughput of every port
- **Selectable queue configurations**
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- **IGMP snooping**
improves network performance through multicast filtering, instead of flooding traffic to all ports
- **Fiber uplink**
provides greater distance connectivity using Gigabit fiber uplinks

Layer 2 switching

Overview

- **VLAN support and tagging**
supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **Spanning Tree Protocol (STP)**
supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **BPDU filtering**
drops BPDU packets when STP is enabled globally but disabled on a specific port
- **Jumbo frame support**
supports up to 10 kilobyte frame size to improve the performance of large data transfers

Layer 3 services

- **Address Resolution Protocol (ARP)**
determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **DHCP relay**
simplifies management of DHCP addresses in networks with multiple subnets

Layer 3 routing

- **NEW Static IPv4/IPv6 routing**
provides basic routing (supporting up to 32 static routes and 8 virtual VLAN interfaces); allows manual configuration of routing

Resiliency and high availability

- **Available redundant power supply**
provides additional PoE of up to 740 W for high-power applications like HP Gigabit Ethernet IntelliJack switches; the HP RPS1600 Redundant Power System (JG136A), sold separately, is only for use with the 1910-24G-PoE (365W) Switch model
- **Link aggregation**
groups together multiple ports (up to a maximum of 2 ports) automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks

Convergence

- **LLDP-MED (Media Endpoint Discovery)**
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **PoE allocations**
supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings
- **Auto voice VLAN**
recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones

Additional information

- **Green initiative support**
provides support for RoHS and WEEE regulation
- **Green IT and power**
improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

Overview

Warranty and support

- **Lifetime Warranty 2.0**

advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†

- **Electronic and telephone support (for Lifetime Warranty 2.0)**

limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to

www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to **www.hp.com/networking/warrantysummary**

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at **www.hp.com/networking/warranty**.

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP 1910-8 Switch	JG536A
<ul style="list-style-type: none">8 RJ-45 autosensing 10/100 ports2 SFP dual-personality 1000 Mbps portsmin=0 \ max=2 SFP Transceivers1U - Height	See Configuration Note: 2,3
HP 1910-8 -PoE+ Switch	JG537A
<ul style="list-style-type: none">8 RJ-45 auto-negotiating 10/100 ports2 SFP dual-personality 1000 Mbps portsmin=0 \ max=2 SFP Transceivers1U - Height	See Configuration Note: 2,3
HP 1910-8G Switch	JG348A
<ul style="list-style-type: none">8 RJ-45 auto-negotiating 10/100/1000 ports1 SFP 1000 Mbps portmin=0 \ max=1 SFP Transceiver1U - Height	See Configuration Note: 4,5
PDU Cable NA/MX/TW/JP	JG348A#B2B
<ul style="list-style-type: none">C15 PDU Jumper Cord (NA/MX/TW/JP)	
PDU Cable ROW	JG348A#B2C
<ul style="list-style-type: none">C15 PDU Jumper Cord (ROW)	
HP 1910-8G-PoE+ (65W) Switch	JG349A
<ul style="list-style-type: none">8 RJ-45 auto-negotiating 10/100/1000 ports1 SFP 1000 Mbps portmin=0 \ max=1 SFP Transceiver1U - Height	See Configuration Note: 4,5
PDU Cable NA/MX/TW/JP	JG349A#B2B
<ul style="list-style-type: none">C15 PDU Jumper Cord (NA/MX/TW/JP)	
PDU Cable ROW	JG349A#B2C
<ul style="list-style-type: none">C15 PDU Jumper Cord (ROW)	
HP 1910-8G-PoE+ (180W) Switch	JG350A
<ul style="list-style-type: none">8 RJ-45 auto-negotiating 10/100/1000 ports1 SFP 1000 Mbps portmin=0 \ max=1 SFP Transceiver1U - Height	See Configuration Note: 4,5
PDU Cable NA/MX/TW/JP	JG350A#B2B

Configuration

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JG350A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-16G Switch

JE005A

- 16 RJ-45 auto-negotiating 10/100/1000 ports
- 4 SFP 1000 Mbps port
- min=0 \ max=4 SFP Transceivers
- 1U - Height

See Configuration
Note:1, 5

PDU Cable NA/MX/TW/JP

JE005A#B2B

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JE005A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-24G-PoE (170W) Switch

JE008A

- 24 RJ-45 auto-negotiating 10/100/1000 ports
- 4 SFP 1000 Mbps ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

See Configuration
Note:1, 5

PDU Cable NA/MX/TW/JP

JE008A#B2B

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JE008A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-24G-PoE (365W) Switch

JE007A

- 24 RJ-45 auto-negotiating 10/100/1000 ports
- 4 SFP 1000 Mbps ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

See Configuration
Note:1, 5

PDU Cable NA/MX/TW/JP

JE007A#B2B

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JE007A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-24G Switch

JE006A

- 24 RJ-45 auto-negotiating 10/100/1000 ports
- 4 SFP 1000 Mbps ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

See Configuration
Note:1, 5

Configuration

PDU Cable NA/MX/TW/JP

JE006A#B2B

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JE006A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-24 Switch

JG538A

- 24 RJ-45 autosensing 10/100 ports
- 2 SFP dual-personality 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

See Configuration
Note:2,3

HP 1910-24-PoE+ Switch

JG539A

- 24 RJ-45 auto-negotiating 10/100 ports
- 2 SFP dual-personality 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

See Configuration
Note:2,3

HP 1910-48G Switch

JE009A

- 48 RJ-45 auto-negotiating 10/100/1000 ports
- 4 SFP 1000 Mbps ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

See Configuration
Note:1, 5

PDU Cable NA/MX/TW/JP

JE009A#B2B

- C15 PDU Jumper Cord (NA/MX/TW/JP)

PDU Cable ROW

JE009A#B2C

- C15 PDU Jumper Cord (ROW)

HP 1910-48 Switch

JG540A

- 48 RJ-45 autosensing 10/100 ports
- 2 RJ-45 autosensing10/100/1000 ports
- 2 SFP 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

See Configuration
Note: 2,3

Configuration

Configuration Rules:

- Note 1
- The following Transceivers install into this switch:
- | | |
|---------------------------------------|--------|
| HP X121 1G SFP LC SX Transceiver | J4858C |
| HP X121 1G SFP LC LX Transceiver | J4859C |
| HP X121 1G SFP RJ45 T Transceiver | J8177C |
| HP X120 1G SFP LC SX Transceiver | JD118B |
| HP X120 1G SFP LC LX Transceiver | JD119B |
| HP X120 1G SFP RJ45 T Transceiver | JD089A |
| HP X125 1G SFP LC LH40 1310nm XCVR | JD061A |
| HP X120 1G SFP LC LH40 1550nm XCVR | JD062A |
| HP X125 1G SFP LC LH70 Transceiver | JD063B |
| HP X120 1G SFP LC BX 10-U Transceiver | JD098B |
| HP X120 1G SFP LC BX 10-D Transceiver | JD099B |
- Note 2
- Localization required. (See Localization Menu for list.)
- Note 3
- The following Transceivers install into this switch:
- | | |
|----------------------------------|--------|
| HP X121 1G SFP LC SX Transceiver | J4858C |
| HP X121 1G SFP LC LX Transceiver | J4859C |
| HP X120 1G SFP LC LX Transceiver | JD119B |
- Note 4
- The following Transceivers install into this switch:
- | | |
|------------------------------------|--------|
| HP X121 1G SFP LC SX Transceiver | J4858C |
| HP X121 1G SFP LC LX Transceiver | J4859C |
| HP X121 1G SFP RJ45 T Transceiver | J8177C |
| HP X120 1G SFP LC SX Transceiver | JD118B |
| HP X120 1G SFP LC LX Transceiver | JD119B |
| HP X120 1G SFP RJ45 T Transceiver | JD089B |
| HP X125 1G SFP LC LH40 1310nm XCVR | JD061A |
| HP X120 1G SFP LC LH40 1550nm XCVR | JD062A |
| HP X125 1G SFP LC LH70 Transceiver | JD063B |
- Note 5
- Localization (Wall Power Cord) required on orders without #B2B or #B2C (PDU Power Cord). (See Localization Menu)

Configuration

Internal or External Power Supplies(Model Dependant)

Power supplies Included

Transceivers

SFP Transceivers

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X121 1G SFP RJ45 T Transceiver	J8177C
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X125 1G SFP LC LH40 1310nm XCVR	JD061A
HP X120 1G SFP LC LH40 1550nm XCVR	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B

Cables

Multi-Mode Cables

HP .5m Multi-mode OM3 LC/LC FC Cable	AJ833A
HP 1m Multi-mode OM3 LC/LC FC Cable	AJ834A
HP 2 m Multimode OM3 LC/LC FC Cable	AJ835A
HP 5 m Multimode OM3 LC/LC FC Cable	AJ836A
HP 15 m Multimode OM3 LC/LC FC Cable	AJ837A
HP 30 m Multimode OM3 LC/LC FC Cable	AJ838A
HP 50 m Multimode OM3 LC/LC FC Cable	AJ839A
HP Premier Flex LC/LC OM4 2f 1m Cbl	QK732A
HP Premier Flex LC/LC OM4 2f 2m Cbl	QK733A
HP Premier Flex LC/LC OM4 2f 5m Cbl	QK734A
HP Premier Flex LC/LC OM4 2f 15m Cbl	QK735A
HP Premier Flex LC/LC OM4 2f 30m Cbl	QK736A
HP Premier Flex LC/LC OM4 2f 50m Cbl	QK737A

Technical Specifications

HP 1910-48G Switch (JE009A)

Ports	48 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination	
Physical characteristics	Dimensions	17.4(w) x 10.24(d) x 1.7(h) in (44.2 x 26.01 x 4.32 cm) (1U height)
	Weight	6.8 lb (3.08 kg)
Memory and processor	Module	ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μ s
	1000 Mb Latency	< 5 μ s
	Throughput	up to 77.4 Mpps (64-byte packets)
	Routing/Switching capacity	104 Gbps
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, non-condensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	10% to 95%, non-condensing
Electrical characteristics	Frequency	50/60 Hz
Achieved Miercom Certified Green Award	Voltage	100-240 VAC
	Maximum power rating	59.8 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	SFP ports and copper ports work simultaneously, independent of each other to give a total of 52 Gigabit-capable ports.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW036E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)	

Technical Specifications

- 3-year, 24x7 SW phone support, software updates (UV807E)
- 3-year, 24x7 SW phone support, software updates (UV789E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)
- Installation with minimum configuration, system-based pricing (UY901E)
- Installation with HP-provided configuration, system-based pricing (UY902E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV805E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW034E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW037E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)
- 4-year, 24x7 SW phone support, software updates (UV790E)
- 4-year, 24x7 SW phone support, software updates (UV808E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV806E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW035E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW038E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)
- 5-year, 24x7 SW phone support, software updates (UV791E)
- 5-year, 24x7 SW phone support, software updates (UV809E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW491E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW039E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW492E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW040E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW493E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW041E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-24G-PoE (365 W) Switch (JE007A)

Ports	24 RJ-45 auto-negotiating 10/100/1000 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE)	
	4 SFP 1000 Mbps ports	
	1 RJ-45 console port to access limited CLI port	
	Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination	
Physical characteristics	Dimensions	17.4(w) x 16.54(d) x 1.7(h) in (44.2 x 42.01 x 4.32 cm) (1U height)
	Weight	6.8 lb (3.08 kg)
Memory and processor	Module	ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 µs

Technical Specifications

	1000 Mb Latency	< 5 μ s
	Throughput	up to 41.7 Mpps (64-byte packets)
	Routing/Switching capacity	56 Gbps
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, non-condensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	10% to 95%, non-condensing
Electrical characteristics	Frequency	50 / 60 Hz
	Voltage	100-240 VAC
	Maximum power rating	523 W
	PoE power	365 W
	Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).</p>
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
Services	<p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW036E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>3-year, 24x7 SW phone support, software updates (UV807E)</p> <p>3-year, 24x7 SW phone support, software updates (UV789E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with minimum configuration, system-based pricing (UW451E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV805E)</p>	

Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW034E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW037E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)
- 4-year, 24x7 SW phone support, software updates (UV790E)
- 4-year, 24x7 SW phone support, software updates (UV808E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV806E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW035E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW038E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)
- 5-year, 24x7 SW phone support, software updates (UV791E)
- 5-year, 24x7 SW phone support, software updates (UV809E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW491E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW039E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW492E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW040E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW493E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW041E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-24G-PoE (170 W) Switch (JE008A)

Ports	24 RJ-45 auto-negotiating 10/100/1000 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE)	
	4 SFP 1000 Mbps ports	
	1 RJ-45 console port to access limited CLI port	
	Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination	
Physical characteristics	Dimensions	17.4(w) x 16.54(d) x 1.7(h) in (44.2 x 42.01 x 4.32 cm) (1U height)
	Weight	6.8 lb (3.08 kg)
Memory and processor	Module	ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μ s
	1000 Mb Latency	< 5 μ s
	Throughput	up to 41.7 Mpps (64-byte packets)
	Routing/Switching capacity	56 Gbps
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)

Technical Specifications

	Operating relative humidity	10% to 90%, non-condensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	10% to 95%, non-condensing
Electrical characteristics	Frequency	50 / 60 Hz
	Voltage	100-240 VAC
	Maximum power rating	255 W
	PoE power	170 W
	Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies.</p>
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
Services	<p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW036E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>3-year, 24x7 SW phone support, software updates (UV807E)</p> <p>3-year, 24x7 SW phone support, software updates (UV789E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV805E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW034E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW037E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>4-year, 24x7 SW phone support, software updates (UV808E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV806E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW035E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW038E)</p>	

Technical Specifications

5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)
 5-year, 24x7 SW phone support, software updates (UV791E)
 5-year, 24x7 SW phone support, software updates (UV809E)
 3 Yr 6 hr Call-to-Repair Onsite (UW491E)
 3 Yr 6 hr Call-to-Repair Onsite (UW039E)
 4 Yr 6 hr Call-to-Repair Onsite (UW492E)
 4 Yr 6 hr Call-to-Repair Onsite (UW040E)
 5 Yr 6 hr Call-to-Repair Onsite (UW493E)
 5 Yr 6 hr Call-to-Repair Onsite (UW041E)
 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-24G Switch (JE006A)

Ports	24 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination												
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>6.8 lb (3.08 kg)</td> </tr> </table>	Dimensions	17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)	Weight	6.8 lb (3.08 kg)								
Dimensions	17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)												
Weight	6.8 lb (3.08 kg)												
Memory and processor	<table border="0"> <tr> <td style="vertical-align: top;">Module</td> <td>ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB</td> </tr> </table>	Module	ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB										
Module	ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB												
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)												
Performance	<table border="0"> <tr> <td style="vertical-align: top;">100 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>up to 41.7 million pps</td> </tr> <tr> <td style="vertical-align: top;">Routing/Switching capacity</td> <td>56 Gbps</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>32 entries</td> </tr> <tr> <td style="vertical-align: top;">MAC address table size</td> <td>8192 entries</td> </tr> </table>	100 Mb Latency	< 5 μ s	1000 Mb Latency	< 5 μ s	Throughput	up to 41.7 million pps	Routing/Switching capacity	56 Gbps	Routing table size	32 entries	MAC address table size	8192 entries
100 Mb Latency	< 5 μ s												
1000 Mb Latency	< 5 μ s												
Throughput	up to 41.7 million pps												
Routing/Switching capacity	56 Gbps												
Routing table size	32 entries												
MAC address table size	8192 entries												
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage relative humidity</td> <td>10% to 95%, non-condensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, non-condensing	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Non-operating/Storage relative humidity	10% to 95%, non-condensing				
Operating temperature	32°F to 113°F (0°C to 45°C)												
Operating relative humidity	10% to 90%, non-condensing												
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Non-operating/Storage relative humidity	10% to 95%, non-condensing												
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Frequency</td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>31.5 W</td> </tr> </table>	Frequency	50/60 Hz	Voltage	100-240 VAC	Maximum power rating	31.5 W						
Frequency	50/60 Hz												
Voltage	100-240 VAC												
Maximum power rating	31.5 W												

Technical Specifications

Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW036E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E) 3-year, 24x7 SW phone support, software updates (UV807E) 3-year, 24x7 SW phone support, software updates (UV789E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E) Installation with minimum configuration, system-based pricing (UY901E) Installation with HP-provided configuration, system-based pricing (UY902E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV805E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW034E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW037E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E) 4-year, 24x7 SW phone support, software updates (UV790E) 4-year, 24x7 SW phone support, software updates (UV808E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV806E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW035E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW038E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E) 5-year, 24x7 SW phone support, software updates (UV791E) 5-year, 24x7 SW phone support, software updates (UV809E) 3 Yr 6 hr Call-to-Repair Onsite (UW491E) 3 Yr 6 hr Call-to-Repair Onsite (UW039E) 4 Yr 6 hr Call-to-Repair Onsite (UW492E) 4 Yr 6 hr Call-to-Repair Onsite (UW040E) 5 Yr 6 hr Call-to-Repair Onsite (UW493E) 5 Yr 6 hr Call-to-Repair Onsite (UW041E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP 1910-16G Switch (JE005A)

Ports	16 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 16 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination												
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>6.8 lb (3.08 kg)</td> </tr> </table>	Dimensions	17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)	Weight	6.8 lb (3.08 kg)								
Dimensions	17.4(w) x 6.3(d) x 1.7(h) in (44.2 x 16 x 4.32 cm) (1U height)												
Weight	6.8 lb (3.08 kg)												
Memory and processor	Module ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB												
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)												
Performance	<table border="0"> <tr> <td style="vertical-align: top;">100 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>up to 29.8 million pps</td> </tr> <tr> <td style="vertical-align: top;">Routing/Switching capacity</td> <td>40 Gbps</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>32 entries</td> </tr> <tr> <td style="vertical-align: top;">MAC address table size</td> <td>8192 entries</td> </tr> </table>	100 Mb Latency	< 5 μ s	1000 Mb Latency	< 5 μ s	Throughput	up to 29.8 million pps	Routing/Switching capacity	40 Gbps	Routing table size	32 entries	MAC address table size	8192 entries
100 Mb Latency	< 5 μ s												
1000 Mb Latency	< 5 μ s												
Throughput	up to 29.8 million pps												
Routing/Switching capacity	40 Gbps												
Routing table size	32 entries												
MAC address table size	8192 entries												
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage relative humidity</td> <td>10% to 95%, non-condensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, non-condensing	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Non-operating/Storage relative humidity	10% to 95%, non-condensing				
Operating temperature	32°F to 113°F (0°C to 45°C)												
Operating relative humidity	10% to 90%, non-condensing												
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Non-operating/Storage relative humidity	10% to 95%, non-condensing												
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Frequency</td> <td>50 / 60 Hz</td> </tr> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>25.1 W</td> </tr> <tr> <td style="vertical-align: top;">Notes</td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	Frequency	50 / 60 Hz	Voltage	100-240 VAC	Maximum power rating	25.1 W	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.				
Frequency	50 / 60 Hz												
Voltage	100-240 VAC												
Maximum power rating	25.1 W												
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.												
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03												
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A												
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB												
Notes	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 20 Gigabit-capable ports.												
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW036E)												

Technical Specifications

3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)
3-year, 24x7 SW phone support, software updates (UV807E)
3-year, 24x7 SW phone support, software updates (UV789E)
1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)
Installation with minimum configuration, system-based pricing (UY901E)
Installation with HP-provided configuration, system-based pricing (UY902E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UV805E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UW034E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW037E)
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)
4-year, 24x7 SW phone support, software updates (UV790E)
4-year, 24x7 SW phone support, software updates (UV808E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UV806E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UW035E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW038E)
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)
5-year, 24x7 SW phone support, software updates (UV791E)
5-year, 24x7 SW phone support, software updates (UV809E)
3 Yr 6 hr Call-to-Repair Onsite (UW491E)
3 Yr 6 hr Call-to-Repair Onsite (UW039E)
4 Yr 6 hr Call-to-Repair Onsite (UW492E)
4 Yr 6 hr Call-to-Repair Onsite (UW040E)
5 Yr 6 hr Call-to-Repair Onsite (UW493E)
5 Yr 6 hr Call-to-Repair Onsite (UW041E)
1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP 1910-8G Switch (JG348A)

Ports	8 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 SFP 1000 Mbps port 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination
Physical characteristics	Dimensions 8.27(w) x 8.27(d) x 1.72(h) in (21 x 21 x 4.36 cm) (1U height) Weight 4.41 lb (2 kg), Fully loaded
Memory and processor	Module ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
Performance	100 Mb Latency < 5 μ s 1000 Mb Latency < 5 μ s Throughput up to 13.4 million pps Routing/Switching capacity 18 Gbps Routing table size 32 entries MAC address table size 8192 entries
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 10% to 90%, non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 10% to 95%, non-condensing
Electrical characteristics	Voltage 100-240 VAC Maximum power rating 14.4 W Frequency 50/60 Hz Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	SFP port and copper ports work simultaneously, independent of each other to give a total of 9 Gigabit-capable ports.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-8G-PoE+ (65W) Switch (JG349A)

Technical Specifications

Ports	8 RJ-45 auto-negotiating 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE, IEEE 802.3at) 1 SFP 1000 Mbps port 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination												
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>6.61 lb (3 kg), Fully loaded</td> </tr> </table>	Dimensions	10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)	Weight	6.61 lb (3 kg), Fully loaded								
Dimensions	10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)												
Weight	6.61 lb (3 kg), Fully loaded												
Memory and processor	Module ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB												
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)												
Performance	<table border="0"> <tr> <td style="vertical-align: top;">100 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>up to 13.4 million pps</td> </tr> <tr> <td style="vertical-align: top;">Routing/Switching capacity</td> <td>18 Gbps</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>32 entries</td> </tr> <tr> <td style="vertical-align: top;">MAC address table size</td> <td>8192 entries</td> </tr> </table>	100 Mb Latency	< 5 μ s	1000 Mb Latency	< 5 μ s	Throughput	up to 13.4 million pps	Routing/Switching capacity	18 Gbps	Routing table size	32 entries	MAC address table size	8192 entries
100 Mb Latency	< 5 μ s												
1000 Mb Latency	< 5 μ s												
Throughput	up to 13.4 million pps												
Routing/Switching capacity	18 Gbps												
Routing table size	32 entries												
MAC address table size	8192 entries												
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage relative humidity</td> <td>10% to 95%, non-condensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, non-condensing	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Non-operating/Storage relative humidity	10% to 95%, non-condensing				
Operating temperature	32°F to 113°F (0°C to 45°C)												
Operating relative humidity	10% to 90%, non-condensing												
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Non-operating/Storage relative humidity	10% to 95%, non-condensing												
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>93 W</td> </tr> <tr> <td style="vertical-align: top;">PoE power</td> <td>65 W</td> </tr> <tr> <td style="vertical-align: top;">Frequency</td> <td>50/60 Hz</td> </tr> </table> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies.</p>	Voltage	100-240 VAC	Maximum power rating	93 W	PoE power	65 W	Frequency	50/60 Hz				
Voltage	100-240 VAC												
Maximum power rating	93 W												
PoE power	65 W												
Frequency	50/60 Hz												
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03												
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A												
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB												
Notes	SFP port and copper ports work simultaneously, independent of each other to give a total of 9 Gigabit-capable ports.												
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.												

Technical Specifications

HP 1910-8G-PoE+ (180W) Switch (JG350A)

Ports	8 RJ-45 auto-negotiating 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE, IEEE 802.3at) 1 SFP 1000 Mbps port 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination												
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>6.61 lb (3 kg), Fully loaded</td> </tr> </table>	Dimensions	10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)	Weight	6.61 lb (3 kg), Fully loaded								
Dimensions	10.24(w) x 11.81(d) x 1.72(h) in (26 x 30 x 4.36 cm) (1U height)												
Weight	6.61 lb (3 kg), Fully loaded												
Memory and processor	Module ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB												
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)												
Performance	<table border="0"> <tr> <td style="vertical-align: top;">100 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>up to 13.4 million pps</td> </tr> <tr> <td style="vertical-align: top;">Routing/Switching capacity</td> <td>18 Gbps</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>32 entries</td> </tr> <tr> <td style="vertical-align: top;">MAC address table size</td> <td>8192 entries</td> </tr> </table>	100 Mb Latency	< 5 μ s	1000 Mb Latency	< 5 μ s	Throughput	up to 13.4 million pps	Routing/Switching capacity	18 Gbps	Routing table size	32 entries	MAC address table size	8192 entries
100 Mb Latency	< 5 μ s												
1000 Mb Latency	< 5 μ s												
Throughput	up to 13.4 million pps												
Routing/Switching capacity	18 Gbps												
Routing table size	32 entries												
MAC address table size	8192 entries												
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/Storage relative humidity</td> <td>10% to 95%, non-condensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, non-condensing	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Non-operating/Storage relative humidity	10% to 95%, non-condensing				
Operating temperature	32°F to 113°F (0°C to 45°C)												
Operating relative humidity	10% to 90%, non-condensing												
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Non-operating/Storage relative humidity	10% to 95%, non-condensing												
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Frequency</td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>228 W</td> </tr> <tr> <td style="vertical-align: top;">PoE power</td> <td>180 W</td> </tr> </table> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies.</p>	Frequency	50/60 Hz	Voltage	100-240 VAC	Maximum power rating	228 W	PoE power	180 W				
Frequency	50/60 Hz												
Voltage	100-240 VAC												
Maximum power rating	228 W												
PoE power	180 W												
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03												
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A												
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB												
Notes	SFP port and copper ports work simultaneously, independent of each other to give a total of 9 Gigabit-capable ports.												
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.												

Technical Specifications

HP 1910-24 Switch (JG538A)

Ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T) 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, with optional module
Physical characteristics	Dimensions 17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height) Weight 4.85 lb (2.2 kg)
Memory and processor	Module MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
Performance	100 Mb Latency < 5 μ s 1000 Mb Latency < 5 μ s Throughput up to 6.6 Mpps (64-byte packets) Routing/Switching capacity 8.8 Gb/s Routing table size 32 entries (IPv4), 32 entries (IPv6) MAC address table size 8192 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 10% to 90%, noncondensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 10% to 95%, noncondensing
Electrical characteristics	Frequency 50/60 Hz Voltage 100-240 VAC Maximum power rating 12 W Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	The HP 1910-24G Switch (JE006A) was formerly sold as the 3Com Baseline Plus 2928 (3CRBSG2893) and may ship with this product labeling. SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.

Technical Specifications

Services Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-8 Switch (JG536A)

Ports	8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T) 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination	
Physical characteristics	Dimensions	10.47(w) x 6.38(d) x 1.73(h) in (26.6 x 16.2 x 4.4 cm) (1U height)
	Weight	2.2 lb (1 kg)
Memory and processor	Module	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μ s
	1000 Mb Latency	< 5 μ s
	Throughput	up to 4.2 Mpps (64-byte packets)
	Routing/Switching capacity	5.6 Gb/s
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	10% to 90%, noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	10% to 95%, noncondensing
Electrical characteristics	Frequency	50/60 Hz
	Voltage	100-240 VAC
	Maximum power rating	8 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	

Technical Specifications

Notes	The HP 1910-24G Switch (JE006A) was formerly sold as the 3Com Baseline Plus 2928 (3CRBSG2893) and may ship with this product labeling. SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-48 Switch (JG540A)

Ports	48 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 2 SFP 1000 Mbps ports 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 1 RJ-45 console port to access limited CLI port Supports a maximum of 48 autosensing 10/100 ports plus 2 1000BASE-X SFP ports plus 2 autosensing 10/100/1000 ports, or a combination
Physical characteristics	Dimensions 17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height) Weight 5.07 lb (2.3 kg)
Memory and processor	Module MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 1.5 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
Performance	100 Mb Latency < 5 μ s 1000 Mb Latency < 5 μ s Throughput up to 13.1 Mpps (64-byte packets) Routing/Switching capacity 17.6 Gb/s Routing table size 32 entries (IPv4), 32 entries (IPv6) MAC address table size 8192 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 10% to 90%, noncondensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 10% to 95%, noncondensing
Electrical characteristics	Frequency 50/60 Hz Voltage 100-240 VAC Maximum power rating 22 W Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition

Technical Specifications

Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	The HP 1910-24G Switch (JE006A) was formerly sold as the 3Com Baseline Plus 2928 (3CRBSG2893) and may ship with this product labeling. SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-8-PoE+ Switch (JG537A)

Ports	8 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full 2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T) 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination												
Physical characteristics	<table> <tr> <td>Dimensions</td> <td>12.99(w) x 9.06(d) x 1.73(h) in (33 x 23 x 4.4 cm) (1U height)</td> </tr> <tr> <td>Weight</td> <td>4.63 lb (2.1 kg)</td> </tr> </table>	Dimensions	12.99(w) x 9.06(d) x 1.73(h) in (33 x 23 x 4.4 cm) (1U height)	Weight	4.63 lb (2.1 kg)								
Dimensions	12.99(w) x 9.06(d) x 1.73(h) in (33 x 23 x 4.4 cm) (1U height)												
Weight	4.63 lb (2.1 kg)												
Memory and processor	Module MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB												
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)												
Performance	<table> <tr> <td>100 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td>1000 Mb Latency</td> <td>< 5 μs</td> </tr> <tr> <td>Throughput</td> <td>up to 4.2 Mpps (64-byte packets)</td> </tr> <tr> <td>Routing/Switching capacity</td> <td>5.6 Gb/s</td> </tr> <tr> <td>Routing table size</td> <td>32 entries (IPv4), 32 entries (IPv6)</td> </tr> <tr> <td>MAC address table size</td> <td>8192 entries</td> </tr> </table>	100 Mb Latency	< 5 μ s	1000 Mb Latency	< 5 μ s	Throughput	up to 4.2 Mpps (64-byte packets)	Routing/Switching capacity	5.6 Gb/s	Routing table size	32 entries (IPv4), 32 entries (IPv6)	MAC address table size	8192 entries
100 Mb Latency	< 5 μ s												
1000 Mb Latency	< 5 μ s												
Throughput	up to 4.2 Mpps (64-byte packets)												
Routing/Switching capacity	5.6 Gb/s												
Routing table size	32 entries (IPv4), 32 entries (IPv6)												
MAC address table size	8192 entries												
Environment	<table> <tr> <td>Operating temperature</td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td>Operating relative humidity</td> <td>10% to 90%, noncondensing</td> </tr> <tr> <td>Non-operating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td>Non-operating/Storage relative humidity</td> <td>10% to 95%, noncondensing</td> </tr> </table>	Operating temperature	32°F to 104°F (0°C to 40°C)	Operating relative humidity	10% to 90%, noncondensing	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Non-operating/Storage relative humidity	10% to 95%, noncondensing				
Operating temperature	32°F to 104°F (0°C to 40°C)												
Operating relative humidity	10% to 90%, noncondensing												
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Non-operating/Storage relative humidity	10% to 95%, noncondensing												
Electrical characteristics	<table> <tr> <td>Frequency</td> <td>50/60 Hz</td> </tr> <tr> <td>Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td>Maximum power rating</td> <td>90 W</td> </tr> <tr> <td>PoE power</td> <td>62 W</td> </tr> </table>	Frequency	50/60 Hz	Voltage	100-240 VAC	Maximum power rating	90 W	PoE power	62 W				
Frequency	50/60 Hz												
Voltage	100-240 VAC												
Maximum power rating	90 W												
PoE power	62 W												

Technical Specifications

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).

Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	The HP 1910-24G Switch (JE006A) was formerly sold as the 3Com Baseline Plus 2928 (3CRBSG2893) and may ship with this product labeling. SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1910-24-PoE+ Switch (JG539A)

Ports	24 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full 2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T) 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination	
Physical characteristics	Dimensions	17.32(w) x 9.37(d) x 1.73(h) in (44 x 23.8 x 4.4 cm) (1U height)
	Weight	7.28 lb (3.3 kg)
Memory and processor	Module	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 µs
	1000 Mb Latency	< 5 µs
	Throughput	up to 6.6 Mpps (64-byte packets)
	Routing/Switching capacity	8.8 Gb/s
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	10% to 90%, non-condensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	10% to 95%, noncondensing

Technical Specifications

Electrical characteristics	Frequency	50/60 Hz
	Voltage	100-240 VAC
	Maximum power rating	220 W
	PoE power	180 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
	PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).	
Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	The HP 1910-24G Switch (JE006A) was formerly sold as the 3Com Baseline Plus 2928 (3CRBSG2893) and may ship with this product labeling. SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Standards and protocols (applies to all products in series)

Device management

RFC 2819 RMON

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s (MSTP)
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.3 Type 10BASE-T
IEEE 802.3ab 1000BASE-T
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3i 10BASE-T
IEEE 802.3x Flow Control
IEEE 802.3z 1000BASE-X

MIBs

RFC 1213 MIB II
RFC 1493 Bridge MIB
RFC 2021 RMONv2 MIB
RFC 2233 Interface MIB
RFC 2233 Interfaces MIB
RFC 2571 SNMP Framework MIB
RFC 2572 SNMP-MPD MIB
RFC 2573 SNMP-Notification MIB

Technical Specifications

RFC 2573 SNMP-Target MIB
RFC 2613 SMON MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2667 IP Tunnel MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 3414 SNMP-User based-SM MIB
RFC 3415 SNMP-View based-ACM MIB
RFC 3418 MIB for SNMPv3

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
IEEE 802.1D (STP)

QoS/Cos

IEEE 802.1P (CoS)

Security

IEEE 802.1X Port Based Network Access Control

Accessories

HP 1910 Switch Series accessories

Transceivers

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X121 1G SFP RJ45 T Transceiver	J8177C
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP RJ45 T Transceiver	JD089B

Cables

HP .5m Multi-mode OM3 LC/LC Optical Cable	AJ833A
HP 1m Multi-mode OM3 LC/LC Optical Cable	AJ834A
HP 2m Multi-mode OM3 LC/LC Optical Cable	AJ835A
HP 5m Multi-mode OM3 LC/LC Optical Cable	AJ836A
HP 15m Multi-mode OM3 LC/LC Optical Cable	AJ837A
HP 30m Multi-mode OM3 LC/LC Optical Cable	AJ838A
HP 50m Multi-mode OM3 LC/LC Optical Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

<p>HP X121 1G SFP LC SX Transceiver (J4858C)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.</p>	<p>Ports</p> <p>Physical characteristics</p>	<p>1 LC 1000BASE-SX port; Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)</p> <p>Weight: 0.04 lb. (0.02 kg)</p> <p>Transceiver form factor: SFP</p>
	<p>Environment</p>	<p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 5% to 85%, noncondensing</p> <p>Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)</p> <p>Altitude: up to 10,000 ft. (3 km)</p>
	<p>Electrical characteristics</p>	<p>Power consumption typical: 0.4 W</p> <p>Power consumption maximum: 0.7 W</p>
	<p>Cabling</p>	<p>Type:</p> <ul style="list-style-type: none"> 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;
		<p>Maximum distance:</p> <ul style="list-style-type: none"> 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth) 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth) 2-500 m (50 µm core diameter, 400 MHz*km bandwidth) 2-550 m (50 µm core diameter, 500 MHz*km bandwidth)
		<p>Cable length: 2-550m</p> <p>Fiber type: Multi Mode</p>
	<p>Services</p>	<p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
<p>HP X121 1G SFP LC LX Transceiver (J4859C)</p> <p>HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.</p>	<p>Ports</p> <p>Physical characteristics</p>	<p>1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm)</p> <p>Weight: 0.04 lb. (0.02 kg)</p>
	<p>Environment</p>	<p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 0% to 85%, noncondensing</p> <p>Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C)</p> <p>Altitude: up to 10,000 ft. (3 km)</p>
	<p>Cabling</p>	<p>Type:</p> <ul style="list-style-type: none"> Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;
		<p>Maximum distance:</p>

Accessory Product Details

- 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth)
- 2-10,000 m (single-mode fiber)

Notes

A mode conditioning patch cord may be needed in some multimode fiber installations.

Wavelength: 1310nm

Power Consumption: < 500mW Typical

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP RJ45 T Transceiver (J8177C)

Ports

1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T); Duplex: full only

Physical characteristics

Dimensions: 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)

Weight: 0.06 lb. (0.03 kg)

HP X121 1G SFP RJ45 T Transceiver: An SFP format gigabit transceiver with RJ45 connectors using 1000BaseT technology.

Environment

Operating temperature: 32°F to 158°F (0°C to 70°C); with 100 LFM airflow over the SFP module

Operating relative humidity: 0% to 95% @ 75°F (25°C), noncondensing

Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)

Nonoperating/Storage relative humidity: 0% to 95% @ 77°F (25°C), noncondensing

Altitude: up to 10,000 ft. (3000 km)

Cabling

Cable type:

1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;

Maximum distance:

- 100 m

Notes

Power consumption is nominally 1 watt.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J8177C 1000Base-T Mini-GBIC" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J8177C Gigabit copper mini-GBIC is not supported on dual-personality ports.

The J8177C is capable of 100 Mb operation. This is supported on only the HP E8200zl, E5400zl, and HP E6200-24G-mGBIC yl Switches using software version K.12.21 or later. Use the "auto-100" port setting to enable 100 Mb operation.

Important: The earlier J8177B does not support 100 Mb operation. When used in the Switch gl 20-Port 10/100/1000 Module (J4908A), the J8177C mini-GBIC can be installed in either the upper or lower mini-GBIC port, but will block access to the other port.

Accessory Product Details

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC SX Transceiver (JD118B)

A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.

Ports

1 LC 1000BASE-SX port

Connectivity

Connector type LC

Wavelength 850 nm

Physical characteristics

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

Electrical characteristics

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

Cabling

Maximum distance:
 • FDDI Grade distance = 220m
 • OM1 = 275m
 • OM2 = 500m
 • OM3 = Not Specified by standard

Cable length up to 550m

Fiber type Multi Mode

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC LX Transceiver (JD119B)

A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF

Ports

1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)

Connectivity

Connector type LC

Wavelength 1300 nm

Physical characteristics

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

Electrical characteristics

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

Cabling

Cable type:
 Either single mode or multimode;

Maximum distance:
 • 550m for Multimode
 • 10km for Singlemode

Fiber type Both

Accessory Product Details

Services Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP RJ45 T Transceiver (JD089B)

Ports 1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)

Connectivity **Connector type** RJ-45

Physical characteristics **Dimensions** 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)

Full configuration weight 0.07 lb. (0.03 kg)

Electrical characteristics **Power consumption typical** 0.8 W

Power consumption maximum 1.0 W

Cabling Cable type:
1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T

Maximum distance:
• 100m

Services Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cabling **Cable type:**
50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:
10Gbps Transfer Rate (Ethernet): 300m

Notes Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0μm Cladding diameter: 125 ± 2.0μm Coating diameter: 245 ± 10μm
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.

Accessory Product Details

- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1 m Multimode OM3 LC/LC Optical Cable
(AJ834A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 2 m Multimode OM3 LC/LC Optical Cable
(AJ835A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 5 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ836A)

Cable type:

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 15 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ837A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 30 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ838A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 50 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ839A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
1m Cable (QK732A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
2m Cable (QK733A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.