

Eaton 5SC UPS

500/750/1000/1500VA



5SC Range



LCD interface

Ideal for protecting:

- Tower Servers
- NAS, Network equipment
- ATMs, Ticket machines, Kiosks



Affordable and reliable protection for small business servers

Easily manageable UPS

- The new LCD interface provides clear status of the UPS key parameters such as input and output voltage, load and battery level, and estimated runtime. Configuration capabilities are also offered for output voltage, audible alarm and sensitivity.
- The 5SC offers USB and serial connectivity. USB port is HID compliant for automatic integration into Windows, Mac OS and Linux.
- Eaton Intelligent Power Protector ® (IPP) software delivered as standard, can be used as point to point power management (USB/Serial) or Network based using IPP as a proxy.

Reliable power protection

- Pure sine wave output: When operating in battery mode the 5SC provides a high quality output signal for any sensitive equipment connected, such as active PFC (power factor corrected) servers.
- Buck and Boost operation corrects a wide range of input voltage variations through continuous regulation, without the use of batteries, and ensures consistent input voltage to the loads protected.
- Stronger, longer battery life: Eaton ABM® battery management technology uses an innovative three-stage charging system that extends battery life by up to 50%.

Flexible integration

- Small size for easy integration even with space constraints (kiosks, cash machines, ticket machines etc.) and up to eight outlets for better flexibility!
- Adjustable input waveform sensitivity to adapt the UPS to specific environment (like Genset).
- Easy battery replacement from front panel to extend UPS life.



Powering Business Worldwide

Eaton 5SC UPS

- 1 LCD Interface :
Clear information on
UPS status and measurements



- 2 Panel for batteries
replacement
3 1 USB port + 1 serial port
4 8 IEC 10A sockets

Eaton 5SC 1500i

| TECHNICAL SPECIFICATIONS | 500 | 750 | 1000 | 1500 |
|--|--|-------------------|-------------------|-------------------|
| Rating (VA/W) | 500 VA / 350 W | 750 VA / 525 W | 1000 VA / 700 W | 1500 VA / 1050 W |
| Format | Tower | Tower | Tower | Tower |
| Electrical Characteristics | | | | |
| Technology | Line-Interactive High Frequency (Sinewave, Booster + Fader) | | | |
| Input voltage and frequency ranges without using batteries | 184V–276V, 45–55Hz (50Hz system), 55–65Hz (60Hz system) | | | |
| Output voltage and frequency | 230V (+6/–10 %) (Adjustable to 220V/230V/240V), 50/60Hz +/-0.1 % (autosensing) | | | |
| Connections | | | | |
| Input | 1 IEC C14 (10A) | | | |
| Outputs | 4 IEC C13 (10A) | 6 IEC C13 (10A) | 8 IEC C13 (10A) | 8 IEC C13 (10A) |
| Batteries | | | | |
| Typical backup times at 50 and 70% load* | 13/9 | 13/9 | 13/9 | 13/9 |
| Battery management | ABM®, Automatic battery test, deep discharge protection | | | |
| Communication | | | | |
| Communication ports | 1 USB port + 1 RS232 serial port (USB and RS232 ports cannot be used simultaneously) | | | |
| Operating conditions, Standards and Approvals | | | | |
| Operating temperature | 0–35°C | 0–35°C | 0–35°C | 0–35°C |
| Noise level | <40dB | <40dB | <40dB | <40dB |
| Safety | IEC/EN 62040-1, UL 1778 | | | |
| EMC, Performance | IEC/EN 62040-2 | | | |
| Approvals | CE, CB report (TUV) | | | |
| Dimensions H x W x D / Weight | | | | |
| Dimensions | 210 x 150 x 240mm | 210 x 150 x 340mm | 210 x 150 x 340mm | 210 x 150 x 410mm |
| Weight | 6.6kg | 10.4kg | 11.1kg | 15.2kg |
| Customer Service & Support | | | | |
| Warranty | 2 years | | | |

* Runtimes are shown at 0.7 power factor. Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

| Part Numbers | 500 | 750 | 1000 | 1500 |
|--------------|---------|---------|----------|----------|
| 5SC | 5SC500i | 5SC750i | 5SC1000i | 5SC1500i |

In the interests of continuous product improvement, all specifications are subject to change without notice.

