

Overview

Models

LSI 9217-4i4e 8-port SAS 6Gb/s RAID Card

EOX20AA

Introduction

Low-profile, four internal and four external port 6Gb/s SATA+ SAS PCIe 3.0 HBA. It is designed to provide high-speed throughput to internal drives and scalability to external storage arrays.

Key Features and Benefits

- Four internal and Four external 6Gb/s SAS +SATA ports
 - 8 lanes of PCI Express 3.0 provides faster signaling for high-bandwidth applications
 - Low-profile form-factor design
 - One x4 internal mini-SAS (SFF8087), One x4 external mini-SAS (SFF8088)
 - Offers Integrated RAID (0, 1, 1E and 10)
 - Fusion-MPT™ 2.0 architecture
 - Support for up to 256 SAS or SATA end devices
-

Compatibility

The LSI 9217 SAS RAID HBA is compatible with the HP Z420 and Z620 workstations.

NOTE: Not all models are available in all regions.

Service and Support

The LSI 9217 SAS HBAs have a one-year limited warranty or the remainder of the warranty of the HP host workstation (whichever is longer) in which they are installed. Technical support is available seven days a week, 24 hours a day by phone, as well as in online support forums. Certain restrictions and exclusions apply.

Technical Specifications

PCI Bus	8 lanes, PCI Express 3.0	
RAID Levels	Offers Integrated RAID (0, 1, 1E and 10)	
PCI Data Burst Transfer Rate	Half Duplex x8, PCIe, 8000 MB/s	
SAS Bandwidth	Half Duplex	600 MB/s per lane
PCI Card Type	3.3V Add-in Card	
PCI Voltage	12 V ± 10%	
PCI Power	9.8W typical, Airflow min 200 LFM	
Bracket	Full height and low profile	
Certification Level	PCI Express 3.0 compliant	
SAS Processor	LSI SAS2308/ Fusion MPT 2.0	
Internal Connectors	One x4 internal mini-SAS (SFF8087)	
External Connectors	One x4 external mini-SAS (SFF8088)	
Maximum Number of SCSI Devices	256 Non-RAID SAS/SATA devices	
LED Indicators	N/A	
Temperature	Operating	0° to 55° C
	Storage	-45° to +105° C
Relative Humidity	Operating	5 to 90% Non-condensing
	Storage	5 to 90% Non-condensing
MTBF	>2,000,000 hours	
Compliances	EMC: Class B-US (CFR 47, P15B); Canada (ICES-003); Japan (V-3/02.04); Europe (EN55022/EN55024); Australia/New Zealand (AS/NZS 3548); Safety: EN60950; RoHS; WEEE	
Operating System Support	Windows 7 Professional 32-bit and 64-bit, Windows 8 Pro 64-bit, Linux SLED and RHEL.	
Kit Contents	Controller card, driver CD, Internal MiniSAS (SFF8087) connectors for use in Z420 and Z620 , user documentation and warranty card.	
Dimensions (HxD)	Low Profile (2.6" x 6.6")	

© Copyright 2013 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.